

IMPACT WRENCHES

Fuji Impact Wrenches are suitable for various fastening and unfastening operations. The combination of high torque and fast run down minimise operator fatigue.

PISTOL GRIP MODELS

Sq. 9.5 mm (3/8") ~ 12.7 mm (1/2") ~ 15.9 mm (5/8")



FW-5PX-6



FW-6PM-1



FW-6PL-1



FW-6PX-5~6



FW-6PH-1~11



FW-8PH-3



FW-10PH-1~2



FW-14PX-5



FW-14PH-1~2



FW-14PH-3

Model	Bolt Size	Recommended Torque Range			Max Torque	Free Speed	Square Drive Size		Overall Length (without socket)		Weight (without socket)		Air Consumption (at Load)		Air Hose Size	
		N.m	kgf.m	ft.lb			N.m	min-1	mm	in	mm	in	kg	lb	m ³ /min	ft ³ /min
FW-5PX-6	M5	8-13	0.8-1.3	5.9-9.6	18	12,000	9.5	3/8	150	529/32	0.80	1.8	0.20	7.1	6.3	1/4
FW-6PM-1	M6	14-26	1.4-2.7	10.3-19.2	32	8,500	9.5	3/8	140	533/64	0.92	2.0	0.53	18.7	9.5	3/8
FW-6PL-1	M6	14-26	1.4-2.7	10.3-19.2	32	10,000	9.5	3/8	175	657/64	0.90	2.0	0.20	7.1	9.5	3/8
FW-6PX-5	M6	11-23	1.1-2.3	8.1-17.0	30	10,000	9.5	3/8	156	69/64	1.20	2.6	0.28	9.9	9.5	3/8
FW-6PX-6	M6	10-18	1.0-1.8	7.4-13.3	25	10,000	9.5	3/8	156	69/64	1.20	2.6	0.28	9.9	9.5	3/8
FW-6PH-1	M8	27-40	2.8-4.1	19.9-29.5	60	9,000	9.5	3/8	147	525/32	1.35	3.0	0.35	12.4	9.5	3/8
FW-6PH-11	M8	27-40	2.8-4.1	19.9-29.5	60	9,000	12.7	1/2	152	6	1.40	3.1	0.35	12.4	9.5	3/8
FW-8PH-3	M10	42-80	4.3-8.2	31.0-59.0	130	7,500	12.7	1/2	162	63/8	1.50	3.3	0.40	14.1	9.5	3/8
FW-10PH-1	M10	63-120	6.4-12.2	46.5-88.5	160	7,500	12.7	1/2	179	73/64	2.00	4.4	0.45	15.8	9.5	3/8
FW-10PH-2	M10	47-93	4.8-9.5	34.7-88.6	113	7,500	12.7	1/2	179	73/64	2.00	4.4	0.45	15.8	9.5	3/8
FW-14PX-5	M14	100-150	10.2-15.3	73.8-110.6	190	6,500	12.7	1/2	197	73/4	3.00	6.6	0.40	14.1	9.5	3/8
FW-14PH-1	M14	85-140	8.7-14.3	62.7-103.3	180	7,500	12.7	1/2	202	715/16	2.56	5.7	0.60	21.2	9.5	3/8
FW-14PH-2	M14	85-140	8.7-14.3	62.7-103.3	180	7,500	12.7	1/2	202	715/16	2.56	5.7	0.60	21.2	9.5	3/8
FW-14PH-3	M14	85-140	8.7-14.3	62.7-103.3	180	7,500	15.9	5/8	202	715/16	2.56	5.7	0.60	21.2	9.5	3/8

*Marked * are oil bath types. *All Models are double clutch types.
*Air Inlet Thread Size: PT or NPT 1/4".